

ClicSeal



Directions for Use:

Before fitting boards together, apply ClicSeal to the top of the tongue of all board edges, both sides and ends.

Make sure to apply a generous quantity of ClicSeal to the top of the tongue to ensure a complete, even seal.

Connect boards together immediately after application. Do not allow ClicSeal to dry before locking boards. After 15 – 20 minutes maximum, remove any surplus from the surface of the boards with a plastic spatula.

Floorboards with ClicSeal on them can be removed and replaced because ClicSeal always remains flexible. There will be no damage from the ClicSeal to the floorboard.

Retailer Opportunity:

ClicSeal can be sold with laminate flooring which is to be fitted into kitchens and hallways.

Features & Benefits:

Clicseal is a joint sealer designed to protect the core of 'click' flooring from moisture and water damage. It will prevent joint swelling and opening.

ClicSeal can be used with all glueless flooring – laminate and engineered wood floors and it is ideal for kitchens, bathrooms and entrances.

One tube of ClicSeal will be sufficient for 10m² of flooring.

ClicSeal does not have to be used on the whole floor but can be used just in those areas where water is likely to be splashed.



UNIKA COLOR PRODUCTS LTD

Unika House, New York Way, New York Industrial Park,
Newcastle upon Tyne, U.K. NE27 0QF

Telephone: +44 (0) 191 259 0033

Fax: +44 (0) 191 257 4525

Email: sales@unika.co.uk www.unika.co.uk

